



Listed 84JM
ZMVV
E129884



200116

Pressure Terminal
Connectors

NRTL Cat. No.
S4

4-14 AL9CU | 90°

(#) FLEX - covers stranding classes within G, H, I/DLO, Metric class 5 and K/MTW. **(##)** mm² sizes within AWG/kcmil ranges are included.

(%) B, K includes flex wires classes B-K, and metric mm² class 2 & 5 in the rated gauge range

(+) Dual wire combinations must be the same wire gauge, stranding type, conductor material and insulation type **(++)** UL Listed ferrules are to be used according to the ferrule manufacturer's instructions. May be field or factory installed.

| Wire Size COPPER (solid to semi-rigid stranded and metric mm ² , ##, +, ++) | Wire Size FLEX COPPER (#, +, ++) | Wire Size ALUMINUM | Torque (all drive means) |
|--|---|------------------------------|--------------------------------|
| 4-6 AWG | N/A | 4-6 AWG | 35 |
| (1) or (2) 8 AWG | N/A | (1) or (2) 8 AWG | 25 |
| (1) or (2) 10-14 AWG SOL, B, C | N/A | (1) 10-12 AWG | 20 |
| (1) or (2) 8 AWG | % B-K Single or twin ferrule | N/A | 25 |
| (1) or (2) 10-14 AWG Single or twin ferrule | % B-K Single or twin ferrule | N/A | 20 |

All Torque in in-lbs. For N-M divide by 8.85.